

Cable tie CCT



Advantages




- Cable tie tapered and rounded for easy insertion
- Robust design, first-class quality
- Suitable for indoor and outdoor use
- Black: UV-resistant
- Halogen free
- RoHS compliant
- Installation temperature: -10°C to +45°C
- Temperature resistance: -40°C to +85°C
- Can be used together with push-in plug InsertFIX and cable tie fasteners TBB, TBL, TBD, TBM

- Packed in a practical bag with EURO punching
- Transparent bag for optimal product presentation






Approvals and certificates



Cable tie CCT






Cable tie CCT natural coloured

Type	Art-No	Width	Length	Ø	Load	€ / 100pcs				Min. sales unit
	natural	W [mm]	L [mm]	≤ [mm]	≤ [kg]		[pcs]	[pcs]	[pcs]	[pcs]
CCT 2,5x100	125100CCT	2,5	100	20,5	8		100	1.000	50.000	1.000
CCT 2,5x150	125150CCT	2,5	150	39,8	8		100	1.000	25.000	1.000
CCT 2,5x200	125200CCT	2,5	200	52,5	8		100	1.000	25.000	1.000
CCT 3,6x140	136140CCT	3,6	140	33,0	18		100	1.000	25.000	1.000
CCT 3,6x200	136200CCT	3,6	200	52,5	18		100	1.000	20.000	1.000
CCT 3,6x300	136300CCT	3,6	300	84,0	18		100	1.000	10.000	1.000
CCT 3,6x370	136370CCT	3,6	370	106,0	18		100	1.000	10.000	1.000
CCT 4,8x200	148200CCT	4,8	200	49,5	22		100	1.000	10.000	1.000
CCT 4,8x250	148250CCT	4,8	250	65,0	22		100	1.000	10.000	1.000
CCT 4,8x300	148300CCT	4,8	300	81,0	22		100	1.000	10.000	1.000
CCT 4,8x370	148370CCT	4,8	370	103,5	22		100	1.000	5.000	1.000
CCT 4,8x430	148430CCT	4,8	430	122,5	22		100	1.000	5.000	1.000
CCT 7,6x150	176150CCT	7,6	150	35,0	55		100	1.000	5.000	100
CCT 7,6x200	176200CCT	7,6	200	50,9	55		100	1.000	5.000	100
CCT 7,6x300	176300CCT	7,6	300	82,8	55		100	1.000	5.000	100
CCT 7,6x365	176365CCT	7,6	365	105,0	55		100	1.000	5.000	100
CCT 7,6x450	176450CCT	7,6	450	130,5	55		100	1.000	5.000	100
CCT 7,6x550	176550CCT	7,6	550	159,0	55		100	1.000	2.000	100
CCT 8,8x760	188760CCT	8,8	760	229,5	80		50	500	1.000	50
CCT 9,0x810	190810CCT	9,0	810	245,0	80		50	500	1.000	50
CCT 12,6x530	1126530CCT	12,6	530	156,0	110		50	500	1.250	50
CCT 12,6x1030	11261030CCT	12,6	1.030	315,0	110		50	500	1.250	50



Cable tie CCT black

Type	Art-No	Width W	Length L	Ø ≤	Load ≤	€ / 100 pcs				Min. sales unit
	black	[mm]	[mm]	[mm]	[kg]		[pcs]	[pcs]	[pcs]	[pcs]
CCT 2,5x100	425100CCT	2,5	100	20,5	8		100	1.000	50.000	1.000
CCT 2,5x150	425150CCT	2,5	150	39,8	8		100	1.000	25.000	1.000
CCT 2,5x200	425200CCT	2,5	200	52,5	8		100	1.000	25.000	1.000
CCT 3,6x140	436140CCT	3,6	140	33,0	18		100	1.000	25.000	1.000
CCT 3,6x200	436200CCT	3,6	200	52,5	18		100	1.000	20.000	1.000
CCT 3,6x300	436300CCT	3,6	300	84,0	18		100	1.000	10.000	1.000
CCT 3,6x370	436370CCT	3,6	370	106,0	18		100	1.000	10.000	1.000
CCT 4,8x200	448200CCT	4,8	200	49,5	22		100	1.000	10.000	1.000
CCT 4,8x250	448250CCT	4,8	250	65,0	22		100	1.000	10.000	1.000
CCT 4,8x300	448300CCT	4,8	300	81,0	22		100	1.000	10.000	1.000
CCT 4,8x370	448370CCT	4,8	370	103,5	22		100	1.000	5.000	1.000
CCT 4,8x430	448430CCT	4,8	430	122,5	22		100	1.000	5.000	1.000
CCT 7,6x150	476150CCT	7,6	150	35,0	55		100	1.000	5.000	100
CCT 7,6x200	476200CCT	7,6	200	50,9	55		100	1.000	5.000	100
CCT 7,6x300	476300CCT	7,6	300	82,8	55		100	1.000	5.000	100
CCT 7,6x365	476365CCT	7,6	365	105,0	55		100	1.000	5.000	100
CCT 7,6x450	476450CCT	7,6	450	130,5	55		100	1.000	5.000	100
CCT 7,6x550	476550CCT	7,6	550	159,0	55		100	1.000	2.000	100
CCT 8,8x760	488760CCT	8,8	760	229,5	80		50	500	1.000	50
CCT 9,0x810	490810CCT	9,0	810	245,0	80		50	500	1.000	50
CCT 12,6x530	4126530CCT	12,6	530	156,0	110		50	500	1.250	50
CCT 12,6x1030	41261030CCT	12,6	1.030	315,0	110		50	500	1.250	50