

# Overview of metal clamps

**[Heavy duty-] Metal clamps**



		RIF	RI	RID	LI	L	D	SIN-FIN
Diameter Ø (mm)		15-60	18-355	18-160	12-42	6-63	50-200	10-130
Coating		blue zinc plated	blue zinc plated	blue zinc plated	yellow zinc plated	blue zinc plated	sendzimir zinc plated	blue zinc plated
Inlay		EPDM	EPDM	EPDM+TPE	EPDM	×	×	×
Halogen free		-	✓	✓	-	-	-	-
RoHS compliant		×	✓	✓	×	×	×	×
Fire resistance		DIN 4102 class B2	DIN 4102 class B2	DIN 4102 class B2	DIN 4102 class B2	-	-	-
Temperature range		-50°C to +110°C	-50°C to +110°C	-50°C to +110°C	-50°C to +110°C	-	-	-
Recommended maximum tension load (kg)		80	80 - 200	100-150	55	50	110	-
Sheet thickness (mm)		1,25	1,5-2,0	1,2-2,0 to +2,5	1,2	1,2	1,25	0,8
Clamp width (mm)		20	20/25	20/25	11/12	11/12	20	9
Connecting thread		M8 + M10	M8 + M10	M8 + M10	M6	M6	M8	×
Applications		Heating pipes, Water pipes	Heating pipes, Water pipes	Sliding EPDM rubber lined pipe clamp for heating pipes or water pipes	Air conditioning, gas or compressed air pipes	Electrical and sanitary	Drainage pipes, PVC pipes, light steel pipes, ventilation pipes	Hose connections
Page		274	275	277	278	279	280	281

# Hose clamp

## SF





### Advantages



- Worm drive clamp for fast and easy tightening around the hose
- Rounded edges to avoid damaging the hose or tube

### SF, zinc plated

Type	Art-No	Pipe-Ø [mm]	Sheet thickness [mm]	Width [mm]	Torque [kg-cm]	€ / 100 pcs	 [pcs]	 [pcs]
SF 10/16	910SF	10-16	0,8	9	2,5		100	900
SF 12/20	912SF	12-20	0,8	9	2,5		100	900
SF 15/25	915SF	15-25	0,8	9	2,5		100	900
SF 20/32	920SF	20-32	0,8	9	3,0		100	900
SF 25/40	925SF	25-40	0,8	9	3,0		100	600
SF 32/50	932SF	32-50	0,8	9	3,0		100	600
SF 40/60	940SF	40-60	0,8	9	3,0		100	–
SF 50/70	950SF	50-70	0,8	9	3,0		50	300
SF 90/110	990SF	90-110	0,8	9	3,0		25	–
SF 100/120	9100SF	100-120	0,8	9	3,0		25	–
SF 130	9130SF	130	0,8	9	3,0		25	–