

**DECLARATION OF PERFORMANCE (DoP)**  
according to Construction Products Regulation (CPR) No 305/2011

**DoPNo. 22/0036 - en**

1. Unique identification code of the product-type: **ResiTHERM® 37**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**ETA-22/0036 (issued 17.02.2022), annex A3**  
**Batch number: see packaging of the product.**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

<b>Generic type</b>	Distance mounting system
<b>For use in</b>	- Perforated or hollow bricks (use <b>category c</b> ) - Un-cracked autoclaved aerated concrete (use <b>category d</b> )
<b>Option / Category</b>	c, d
<b>Loading</b>	Static or quasi-static
<b>Material</b>	ResiTHERM 37 plug (all lengths) -> Polyamide PA 6 with glass fibers  M12 threaded rod or M12 screw -> Stainless steel A4 according to EN 10088-3:2014, material 1.4401 or 1.4571, strength class 70 or: -> Steel, electrogalvanized or hot-dip galvanized, property class 5.8  The ResiTHERM 37 is to be used together with the injection mortar CELO ResiFIX VYSF: see ETA-15/0320
<b>Temperature range if applicable</b>	-40°C to +40°C (max. long-term temp. +24°C, max. short-term temp. +40°C)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**CELO Befestigungssysteme GmbH**  
**Industriestrasse 6**  
**86551 Aichach, Germany**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **system 2+**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
**ETA Danmark A/S**

issued:

**ETA-22/0036 (issued 17.02.2022),**

on the basis of

**EAD 331985-00-0604 – Distance mounting system**

The notified body **0672** performed under **system 2+**:

- **Initial inspection of the factory and factory production control,**
- **continuous monitoring, assessment and approval of factory production control.**

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
Resistance to failure under tension loading in masonry	TR077:2021	ETA-22/0036 (issued 17.02.2021), Annex C1	<b>EAD 331985-00-0604 – Distance mounting system</b>
Resistance to failure under shear loading in masonry	TR077:2021	ETA-22/0036 (issued 17.02.2021), Annex C2	
Resistance to pull-out under tension loading	TR077:2021	ETA-22/0036 (issued 17.02.2021), Annex C2	
Displacements under short term and long-term loading	TR077:2021	ETA-22/0036 (issued 17.02.2021), Annex C3, C4	
Minimum edge distance and spacing	TR077:2021	ETA-22/0036 (issued 17.02.2021), Annex B2	
Fire resistance		No performance determined	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



**Achim Ruppertz**  
Marketing and Technical Manager



**Aichach, 17.02.2022**