

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. A**

Revision date: 10.10.2023

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

ResiFIX VYSF Cool, Comp. A

UFI: 2E20-C03C-S003-CT38

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Adhesive mortar for fastening elements A-component (resin)

**Uses advised against**

no restriction

**1.3. Details of the supplier of the safety data sheet**

Company name: CELO Befestigungssysteme GmbH

Street: Industriestr. 6

Place: D-86551 Aichach

Telephone: +49 (0) 8251 90485 0

Telefax: +49 (0) 8251 90485 49

e-mail: info@celofixings.com

**1.4. Emergency telephone number:**

+49 (0) 89 19240 Giftnotruf München (24 h, German and English)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**GB CLP Regulation**

Eye Irrit. 2; H319

Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

**GB CLP Regulation**

**Hazard components for labelling**

Methacrylic acid, monoester with propane-1,2-diol;

Tetramethylene dimethacrylate;

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]

**Signal word:** Warning

**Pictograms:**



**Hazard statements**

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## Safety Data Sheet

according to UK REACH Regulation

### ResiFIX VYSF Cool, Comp. A

Revision date: 10.10.2023

Page 2 of 13

P501 Dispose of contents/container to an approved waste disposal plant in accordance with local/national regulation.

#### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. (--> UK REACH)

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (GB CLP Regulation)	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	1 - < 10 %
	248-666-3	01-2119490226-37
	Eye Irrit. 2, Skin Sens. 1; H319 H317	
2082-81-7	Tetramethylene dimethacrylate	5 - < 20 %
	218-218-1	01-2119967415-30
	Skin Sens. 1B; H317	
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	< 1,25 %
	254-075-1	01-2119980937-17
	Acute Tox. 2, Eye Irrit. 2, Aquatic Chronic 3; H300 H319 H412	
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	< 0,5 %
	911-490-9	01-2119979579-10
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H302 H315 H318 H317 H412	

Full text of H and EUH statements: see section 16.

##### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
27813-02-1	248-666-3	Methacrylic acid, monoester with propane-1,2-diol	1 - < 10 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 2000 mg/kg	
2082-81-7	218-218-1	Tetramethylene dimethacrylate	5 - < 20 %
		dermal: LD50 = > 3000 mg/kg; oral: LD50 = 10066 mg/kg	
38668-48-3	254-075-1	1,1'-(p-Tolylimino)dipropan-2-ol	< 1,25 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 25 - < 200 mg/kg	
-	911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	< 0,5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 619 mg/kg	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

## Safety Data Sheet

according to UK REACH Regulation

### ResiFIX VYSF Cool, Comp. A

Revision date: 10.10.2023

Page 3 of 13

#### General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

#### 4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.  
Causes serious eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Foam  
Extinguishing powder  
Water spray jet  
Carbon dioxide (CO<sub>2</sub>)

##### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic  
Carbon monoxide

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

#### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Use personal protective equipment as required. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

##### Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. A**

Revision date: 10.10.2023

Page 4 of 13

taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

**Advice on general occupational hygiene**

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Wash hands thoroughly after handling. When using do not eat, drink or smoke.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

**Hints on joint storage**

Do not use for products which come into contact with the food stuffs.

**Further information on storage conditions**

storage temperature: -20 - +25°C

**7.3. Specific end use(s)**

Adhesive mortar for fastening elements A-component (resin)

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

## Safety Data Sheet

according to UK REACH Regulation

### ResiFIX VYSF Cool, Comp. A

Revision date: 10.10.2023

Page 5 of 13

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
	Worker DNEL, long-term	inhalation	systemic	14,7 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	8,8 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day
2082-81-7	Tetramethylene dimethacrylate			
	Worker DNEL, long-term	inhalation	systemic	14,5 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	4,3 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol			
	Worker DNEL, long-term	inhalation	systemic	2 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	0,6 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,3 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	0,3 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	0,4 mg/m <sup>3</sup>
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]			
	Worker DNEL, long-term	inhalation	systemic	9,8 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	1,4 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m <sup>3</sup>
	Consumer DNEL, long-term	oral	systemic	0,83 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	0,83 mg/kg bw/day

## Safety Data Sheet

according to UK REACH Regulation

### ResiFIX VYSF Cool, Comp. A

Revision date: 10.10.2023

Page 6 of 13

#### PNEC values

CAS No	Substance	Value
Environmental compartment		
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	
Freshwater		0,904 mg/l
Marine water		0,904 mg/l
Freshwater sediment		6,28 mg/kg
Marine sediment		6,28 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,727 mg/kg
2082-81-7	Tetramethylene dimethacrylate	
Freshwater		0,043 mg/l
Marine water		0,004 mg/l
Freshwater sediment		3,12 mg/kg
Marine sediment		0,312 mg/kg
Micro-organisms in sewage treatment plants (STP)		2 mg/l
Soil		0,573 mg/kg
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	
Freshwater		0,017 mg/l
Marine water		0,0017 mg/l
Freshwater sediment		0,0783 mg/kg
Marine sediment		0,0072 mg/kg
Soil		0,005 mg/kg
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]	
Freshwater		0,048 mg/l
Marine water		0,005 mg/l
Freshwater sediment		0,12 mg/kg
Marine sediment		0,12 mg/kg

#### Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

#### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye/face protection. Wear safety glasses.

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. A**

Revision date: 10.10.2023

Page 7 of 13

**Hand protection**

Disposable gloves  
Recommended material: NBR (Nitrile rubber)  
Breakthrough time: > 480 min  
Thickness of the glove material: > 0,2 mm  
DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	solid (pasty)	
Colour:	light beige	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		Non-flammable.
Lower explosion limits:		not applicable
Upper explosion limits:		not applicable
Flash point:		not applicable
Auto-ignition temperature:		not applicable
Decomposition temperature:		No data available
pH-Value:		The study does not need to be conducted because the substance is known to be insoluble in water.
Viscosity / kinematic:		not applicable
Water solubility:		The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents		
No data available		
Partition coefficient n-octanol/water:		not applicable
Vapour pressure:		No data available
Density (at 20 °C):		1,54 g/cm <sup>3</sup>
Relative vapour density:		not applicable
Particle characteristics:		No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

**Explosive properties**

The product is not: Explosive.

**Self-ignition temperature**

Solid: not determined

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. A**

Revision date: 10.10.2023

Page 8 of 13

Oxidizing properties  
Not oxidising.

**Other safety characteristics**

Evaporation rate:

No data available

Solid content:

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Response: Oxidising agent, strong

**10.4. Conditions to avoid**

none

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) 2260,4 mg/kg



## Safety Data Sheet

according to UK REACH Regulation

### ResiFIX VYSF Cool, Comp. A

Revision date: 10.10.2023

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
2082-81-7	Tetramethylene dimethacrylate				
	oral	LD50 10066 mg/kg	Rat		
	dermal	LD50 > 3000 mg/kg	Rabbit		
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol				
	oral	LD50 > 25 - < 200 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]				
	oral	LD50 619 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

May cause an allergic skin reaction. (Methacrylic acid, monoester with propane-1,2-diol; Tetramethylene dimethacrylate; Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino])

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

## SECTION 12: Ecological information

### 12.1. Toxicity

The product is not: Ecotoxic.

**ResiFIX VYSF Cool, Comp. A**

Revision date: 10.10.2023

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol					
	Acute algae toxicity	ErC50 > 97,2 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 > 143 mg/l	48 h	Daphnia magna (Big water flea)		
2082-81-7	Tetramethylene dimethacrylate					
	Acute algae toxicity	ErC50 9,79 mg/l	72 h	Desmodesmus subspicatus		
	Crustacea toxicity	NOEC 5,09 mg/l	21 d	Daphnia magna (Big water flea)		
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol					
	Acute fish toxicity	LC50 17 mg/l	96 h	Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50 245 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 28,8 mg/l	48 h	Daphnia magna (Big water flea)		
	Algae toxicity	NOEC 57,8 mg/l	72 d	Desmodesmus subspicatus		OECD 201
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]					
	Acute fish toxicity	LC50 > 100 mg/l	96 h			
	Acute algae toxicity	ErC50 > 100 mg/l	72 h			
	Acute crustacea toxicity	EC50 48 mg/l	48 h			

**12.2. Persistence and degradability**

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
	OECD 301C	81%	28	
2082-81-7	Tetramethylene dimethacrylate			
	OECD 310	84 %	28	

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	0,97
2082-81-7	Tetramethylene dimethacrylate	3,1
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	2,1
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	2,17

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. A**

Revision date: 10.10.2023

Page 11 of 13

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.  
The product has not been tested.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations.  
Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - used product**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. A**

Revision date: 10.10.2023

Page 12 of 13

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No information available.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)  
(SEVESO III):**Additional information**

VOC content: 13,0 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**ADR: Accord européen sur le transport des marchandises dangereuses par route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

ErC50: EC50 in terms of reduction of growth rate

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. A**

Revision date: 10.10.2023

Page 13 of 13

vPvB: very persistent and very bioaccumulative  
 PNEC: Predicted No Effect Concentration  
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals  
 RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)  
 VOC: Volatile organic compound  
 Aquatic Chronic 3: Long-term aquatic hazard, Category 3  
 Acute Tox. 2: Acute toxicity, Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation, Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2  
 Skin Sens. 1: Skin sensitization, Category 1  
 STOT SE 3: Specific target organ toxicity (single exposure), Category 3

**Key literature references and sources for data**

Website European Chemicals Agency: <https://echa.europa.eu>

Data sources: Supplier

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

**Relevant H and EUH statements (number and full text)**

H300 Fatal if swallowed.  
 H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H412 Harmful to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. B**

Revision date: 10.10.2023

Page 1 of 11

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

ResiFIX VYSF Cool, Comp. B

UFI: MR10-90K6-A005-22ER

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

compound mortar B-component (hardener)

**Uses advised against**

no restriction

**1.3. Details of the supplier of the safety data sheet**

Company name: CELO Befestigungssysteme GmbH

Street: Industriestr. 6

Place: D-86551 Aichach

Telephone: +49 (0) 8251 90485 0

Telefax: +49 (0) 8251 90485 49

e-mail: info@celofixings.com

**1.4. Emergency telephone number:** +49 (0) 89 19240 Giftnotruf München (24 h, German and English)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Eye Irrit. 2; H319

Skin Sens. 1; H317

STOT RE 2; H373

Aquatic Acute 1; H400

Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Dibenzoyl peroxide

**Signal word:** Warning**Pictograms:****Hazard statements**

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## Safety Data Sheet

according to UK REACH Regulation

### ResiFIX VYSF Cool, Comp. B

Revision date: 10.10.2023

Page 2 of 11

P501 Dispose of contents/container to an approved waste disposal plant in accordance with local/national regulation.

#### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. (--> UK REACH)

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
94-36-0	Dibenzoyl peroxide			5 - < 15 %
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

##### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
94-36-0	202-327-6	Dibenzoyl peroxide	5 - < 15 %
	oral: LD50 = > 5000 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10		

##### Further Information

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

##### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

##### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

##### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. B**

Revision date: 10.10.2023

Page 3 of 11

**4.2. Most important symptoms and effects, both acute and delayed**

May cause an allergic skin reaction.  
Causes serious eye irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Foam  
Extinguishing powder  
Water spray jet  
Carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Pyrolysis products, toxic  
Carbon monoxide

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.  
Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

**Additional information**

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.  
Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up****For cleaning up**

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand  
Treat the recovered material as prescribed in the section on waste disposal.  
Retain contaminated washing water and dispose it.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.  
Wear personal protection equipment (refer to section 8).  
Avoid contact with skin, eyes and clothes.



**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. B**

Revision date: 10.10.2023

Page 4 of 11

When using do not eat, drink or smoke.  
Wash hands thoroughly after handling.  
Take off contaminated clothing and wash it before reuse.

**Advice on general occupational hygiene**

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.  
Wash hands thoroughly after handling. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed.  
Store in a place accessible by authorized persons only.  
Keep only in the original container in a cool, well-ventilated place.

**Hints on joint storage**

Do not store together with: Oxidising agent, strong  
Do not use for products which come into contact with the food stuffs.

**Further information on storage conditions**

Keep container tightly closed in a cool place.  
storage temperature: 5 - 25°C

**7.3. Specific end use(s)**

see section 1.2

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
94-36-0	Dibenzoyl peroxide			
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	13,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	39 mg/m <sup>3</sup>

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
94-36-0	Dibenzoyl peroxide	
Freshwater		0,00002 mg/l
Marine water		0,000002 mg/l
Freshwater sediment		0,013 mg/kg
Marine sediment		0,001 mg/kg

**Additional advice on limit values**

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. B**

Revision date: 10.10.2023

Page 5 of 11

not relevant for this product.

**8.2. Exposure controls**



**Appropriate engineering controls**

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear eye/face protection. Wear safety glasses.

**Hand protection**

Disposable gloves  
Recommended material: NBR (Nitrile rubber)  
Breakthrough time: > 480 min  
Thickness of the glove material: > 0,2 mm  
DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	solid (pasty)	
Colour:	black	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		Combustible
Lower explosion limits:		not applicable
Upper explosion limits:		not applicable
Flash point:		not applicable
Auto-ignition temperature:		not applicable
Decomposition temperature:	Start of decomposition:	>35 °C
pH-Value:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Viscosity / kinematic:		not applicable
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	

## Safety Data Sheet

according to UK REACH Regulation

### ResiFIX VYSF Cool, Comp. B

Revision date: 10.10.2023

Page 6 of 11

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

not applicable

Vapour pressure:

No data available

Density (at 20 °C):

 1,59 g/cm<sup>3</sup>

Relative vapour density:

not applicable

Particle characteristics:

No data available

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Self-ignition temperature

Solid:

not applicable

Oxidizing properties

Not oxidising.

Available oxygen content: &lt; 0,74%

##### Other safety characteristics

Evaporation rate:

No data available

Solid content:

No data available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

see section 10.3

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

#### 10.4. Conditions to avoid

see section 7.2

#### 10.5. Incompatible materials

Oxidising agent, strong

#### 10.6. Hazardous decomposition products

Benzoic acid

Benzene

Biphenyl

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

##### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
94-36-0	Dibenzoyl peroxide				
	oral	LD50 > 5000 mg/kg	Rat		

##### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

**ResiFIX VYSF Cool, Comp. B**

Revision date: 10.10.2023

Page 7 of 11

**Sensitising effects**

May cause an allergic skin reaction. (Dibenzoyl peroxide)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (Quartz (respirable))

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards**
**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**SECTION 12: Ecological information**
**12.1. Toxicity**

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus )

IC10: (0 - 72 h) = 30 mg/l

IC50: (0 - 72 h) = 150 mg/l

OECD 202 (Daphnia magna)

EC0/NOEC (48h) = 100 mg/l

EC50 (48h) = &gt;500 mg/l

EC100 (48h) = &gt;&gt;500 mg/l

OECD 203 (Danio rerio)

LC0/NOEC (96 h) : 250 mg/l

LC50 (96 h) : &gt; 500 mg/l

LC100 (96 h) : &gt;&gt; 500 mg/l

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
94-36-0	Dibenzoyl peroxide					
	Acute fish toxicity	LC50 mg/l	0,0602	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50 mg/l	0,0711	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50 mg/l	0,11	48 h	Daphnia magna (Big water flea)	OECD 202
	Algae toxicity	NOEC mg/l	0,02	3 d	Pseudokirchneriella subcapitata	OECD 201
	Crustacea toxicity	NOEC mg/l	0,001	21 d	Daphnia magna (Big water flea)	OECD 211
	Acute bacteria toxicity	(EC50	35 mg/l)	0,5 h		OECD 209

**12.2. Persistence and degradability**

The product has not been tested.

## Safety Data Sheet

according to UK REACH Regulation

### ResiFIX VYSF Cool, Comp. B

Revision date: 10.10.2023

Page 8 of 11

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD criteria).			

#### **12.3. Bioaccumulative potential**

The product has not been tested.

#### **Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

#### **12.4. Mobility in soil**

The product has not been tested.

#### **12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

#### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations.

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

##### **List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **List of Wastes Code - used product**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. B**

Revision date: 10.10.2023

Page 9 of 11

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No information available.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)  
(SEVESO III):**Additional information**

VOC content: 4,3 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. B**

Revision date: 10.10.2023

Page 10 of 11

**SECTION 16: Other information**

**Abbreviations and acronyms**

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation  
(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)  
ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
CAS: Chemical Abstracts Service  
CLP: Classification, Labeling and Packaging  
DMEL: Derived Minimal Effect level  
DNEL: Derived No Effect Level  
EC50: Effective concentration, 50%  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)  
ICAO: International Civil Aviation Organization  
IC50: Inhibitory concentration, 50%  
IMDG: International Maritime Code for Dangerous Goods  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%  
NOEC: No Observed Effect Concentration  
OECD: Organisation for Economic Co-operation and Development  
PBT: persistent, bioaccumulative and toxic  
vPvB: very persistent and very bioaccumulative  
PNEC: Predicted No Effect Concentration  
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals  
RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)  
VOC: Volatile organic compound  
Aquatic Acute 1: Acute aquatic hazard, Category 1  
Aquatic Chronic 1: Long-term aquatic hazard, Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation, Category 2  
Skin Sens. 1: Skin sensitization, Category 1  
Org. Perox. B: Organic Peroxides, Type B

**Key literature references and sources for data**

Website European Chemicals Agency: <https://echa.europa.eu>  
Data sources: Supplier

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

**Relevant H and EUH statements (number and full text)**

H241 Heating may cause a fire or explosion.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

**Safety Data Sheet**

according to UK REACH Regulation

**ResiFIX VYSF Cool, Comp. B**

Revision date: 10.10.2023

Page 11 of 11

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*