

**DECLARATION OF PERFORMANCE (DoP)**  
**DoPNo. 2022/A22/01**

**1. Unique identification code of the product-type:**

Quick-fix anchor „BAP”

...

**2. Type, batch or serial and lot number or any other element allowing identification of the construction product as required pursuant to Article 275/2013 (VII. 16).**

The type and the lot number can be found on the packaging of the product ...

**3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Area of application	design of fastening systems	
Product identification number (with size code):	BAP Quick-fix anchor 6x45 (9645BAP)	MSZ EN 24102:2011
	BAP Quick-fix anchor 6x60 (9660BAP)	
	BAP Quick-fix anchor 6x80 (9645BAP)	MSZ EN 1363-1:2013
	BAP Quick-fix anchor r 6x85 (9685BAP)	
	BAP Quick-fix anchor 6x100 (96100BAP)	EAD 330232-00-0601:2016

...

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 275/2013 (VII. 16) edict:**

CELO, Roselló, 7 – Pol.Ind. La Bruguera  
08211 Castellar del Vallés, Barcelona, Spanyolország

...

**5. System or systems for assessing and verifying the constancy and the performance of construction products:**

2+ Systems

...

**6. ÉMI Non-Profit Limited Liability Company for Quality Control and Innovation in Building, H-2000 Szentendre, Dózsa György út 26., has issued the National Technical Assessment No. A22 / 2018, according to this document, ÉMI Non-Profit Lic., H-2000 Szentendre, Dózsa György út 26. is a designated body which does:**

- the definition of the product type,
  - random testing of the product,
  - basic inspection of the manufacturing plant and of the factory production control,
  - continuous surveillance, inspection and assessment of factory production control
- performed in the 2+ system and issued the National Technical Assessment of the product under number A22 / 2018.

7. Declared performance

Tensile load capacity (ceiling mounting)		MSZE 24102 MSZ EN 1363-1 MSZ EN 13501-1
Fire resistant usage for 120 minutes (R120)	<u>on reinforced concrete</u>	
Non-fire resistant usage <u>on reinforced concrete</u>	<u>C 20/25 Tension Nper [kN]:</u> 3,6 kN  <u>C 20/25 Shear Vper [kN]:</u> 3,0 kN	
Raw material Thickness of the zinc layer Fire class	Galvanized Steel ≥ 7	
Surface treatment, corrosion protection	zinc plating	

The performance of the product defined in points 1. and 2. , suits to the declared performance indicated in point 7. The manufacturer specified in point 4. is responsible for this declaration of performance.

Date of issue: 12.01.2022.

Signing person in the name and on behalf of the manufacturer:



.....

**Angel Copete**  
Technical Manager  
Celo SA



.....

**Lukács Ákos**  
Product Manager  
Celo Hungária Kft.