

ResiFIX Pure Epoxy BRSF, Comp. A

Revision date: 11.07.2019

Product code: SDB0007

Page 2 of 11

P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.

Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Additional advice on labelling

For distribution to the general public:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of the reach of children.

2.3. Other hazards

People who are allergic to epoxide should avoid the use of the product.

Use only outdoors or in a well-ventilated area.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1675-54-3	bis-[4-(2,3-epoxypropoxy)phenyl]propane			25-50 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
9003-36-5	Bisphenol-F-epichlorohydrin resin MW <= 700			10-20 %
	500-006-8		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411			
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane			10-20 %
	240-260-4		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412			
	Alkyl Ester (Ref.: 722 43/00/2012.0028, Germany)			1-10 %
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids

ResiFIX Pure Epoxy BRSF, Comp. A

Revision date: 11.07.2019

Product code: SDB0007

Page 3 of 11

apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam.

Extinguishing powder

Water spray jet

Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

ResiFIX Pure Epoxy BRSF, Comp. A

Revision date: 11.07.2019

Product code: SDB0007

Page 4 of 11

Avoid contact with skin, eyes and clothes.
When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep container tightly closed.
Store in a place accessible by authorized persons only.
Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong
Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5 - 35°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
9003-36-5	Bisphenol-F-epichlorohydrin resin MW <= 700			
	Worker DNEL, acute	dermal	local	8,3 mg/cm ²
	Worker DNEL, long-term	dermal	systemic	104,15 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	29,39 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	62,5 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	8,7 mg/m ³
	Consumer DNEL, long-term	oral	systemic	6,25 mg/kg bw/day
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane			
	Worker DNEL, long-term	dermal	systemic	2,8 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	2,9 mg/m ³

ResiFIX Pure Epoxy BRSF, Comp. A

Revision date: 11.07.2019

Product code: SDB0007

Page 5 of 11

PNEC values

CAS No	Substance	Value
Environmental compartment		
9003-36-5	Bisphenol-F-epichlorohydrin resin MW <= 700	
Freshwater		0,003 mg/l
Marine water		0,0003 mg/l
Freshwater sediment		0,294 mg/kg
Marine sediment		0,0294 mg/kg
Secondary poisoning		0,0254 mg/l
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,237 mg/kg
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane	
Freshwater		0,0115 mg/l

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

Eye/face protection

Wear eye protection/face protection. Safety goggles with side shields are recommended.

Hand protection

Recommended material: NBR (Nitrile rubber)
 Breakthrough time: > 480 min
 Thickness of the glove material: 0,7 mm
 DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles)

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state: Paste
 Colour: light beige

ResiFIX Pure Epoxy BRSF, Comp. A

Revision date: 11.07.2019

Product code: SDB0007

Page 6 of 11

pH-Value: not determined

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: not determined

Flash point: not applicable

Flammability

Solid: not determined

Gas: not applicable

Lower explosion limits: not determined

Upper explosion limits: not determined

Auto-ignition temperature

Solid: not determined

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 1,49 g/cm³

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

Keep away from: Oxidizing agent

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

ResiFIX Pure Epoxy BRSF, Comp. A

Revision date: 11.07.2019

Product code: SDB0007

Page 7 of 11

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
9003-36-5	Bisphenol-F-epichlorohydrin resin MW <= 700				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane				
	oral	LD50 8500 mg/kg	Rat		
	dermal	LD50 >4900 mg/kg	Rabbit		
	Alkyl Ester (Ref.: 722 43/00/2012.0028, Germany)				
	oral	LD50 20700 mg/kg	Mouse		
	dermal	LD50 2000 mg/kg	Rabbit		

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
9003-36-5	Bisphenol-F-epichlorohydrin resin MW <= 700					
	Acute fish toxicity	LC50 2,54 mg/l	96 h	Carassius auratus (goldfish)		
	Acute crustacea toxicity	EC50 2,55 mg/l	48 h	Daphnia pulex (water flea)		
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane					
	Acute fish toxicity	LC50 30 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

ResiFIX Pure Epoxy BRSF, Comp. A

Revision date: 11.07.2019

Product code: SDB0007

Page 8 of 11

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Advice on disposal

The following waste code numbers from the European Waste Catalog (EWC) are considered as recommendations.

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product


080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number:	UN 3077
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol A/F Epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9



Classification code:	M7
Special Provisions:	274 335 375 601
Limited quantity:	5 kg
Excepted quantity:	E1
Transport category:	3
Hazard No:	90
Tunnel restriction code:	E

Other applicable information (land transport)

No dangerous goods in packaging until 5 kg according special instruction 375 ADR/RID

Inland waterways transport (ADN)

14.1. UN number:	UN 3077
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol A/F Epoxy resin)

according to Regulation (EC) No 1907/2006

ResiFIX Pure Epoxy BRSF, Comp. A


Revision date: 11.07.2019

Product code: SDB0007

Page 9 of 11

14.3. Transport hazard class(es): 9**14.4. Packing group:** III

Hazard label: 9



Classification code: M7

Special Provisions: 274 335 375 601

Limited quantity: 5 kg


Excepted quantity: E1

Other applicable information (inland waterways transport)

No dangerous goods in packaging until 5kg according special instruction 375 ADN

Marine transport (IMDG)**14.1. UN number:** UN 3077**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Bisphenol A/F Epoxy resin)**14.3. Transport hazard class(es):** 9**14.4. Packing group:** III

Hazard label: 9



Special Provisions: 274, 335, 966, 967, 969

Limited quantity: 5 kg

Excepted quantity: E1


EmS: F-A, S-F

Other applicable information (marine transport)

No dangerous goods in packaging until 5kg according 2.10.2.7 IMDG-Code

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number:** UN 3077**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Bisphenol A/F Epoxy resin)**14.3. Transport hazard class(es):** 9**14.4. Packing group:** III

Hazard label: 9



Special Provisions: A97 A158 A179 A197

Limited quantity Passenger: 30 kg G

Passenger LQ: Y956

Excepted quantity: E1

IATA-packing instructions - Passenger: 956

IATA-max. quantity - Passenger: 400 kg

IATA-packing instructions - Cargo: 956

IATA-max. quantity - Cargo: 400 kg

Other applicable information (air transport)

No dangerous goods in packaging until 5kg according A197 IATA-DGA

ResiFIX Pure Epoxy BRSF, Comp. A

Revision date: 11.07.2019

Product code: SDB0007

Page 10 of 11

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes


14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Information according to 2012/18/EU E2 Hazardous to the Aquatic Environment (SEVESO III):

Additional information

VOC content: 0,9 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	2 - clearly water contaminating
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information
Changes

This data sheet contains changes from the previous version in section(s): 1.

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Dangerous Goods Code

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic

ResiFIX Pure Epoxy BRSF, Comp. A

Revision date: 11.07.2019

Product code: SDB0007

Page 11 of 11

vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Chronic 2: Long-term aquatic hazard, Category 2

Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitization, Category 1

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

ResiFIX Pure Epoxy BRSF, Comp. B

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name:	CELO Befestigungssysteme GmbH	
Street:	Industriestr. 6	
Place:	D-86551 Aichach	
Telephone:	+49 (0) 8251 90485 0	Telefax: +49 (0) 8251 90485 49
e-mail:	info@celofixings.com	

1.4. Emergency telephone number: +49 (0) 89 19240 Giftnotruf München (24 h, German and English)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Respiratory or skin sensitisation: Skin Sens. 1

Germ cell mutagenicity: Muta. 2

Reproductive toxicity: Repr. 1B

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May damage fertility.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

3-Aminomethyl-3,5,5-trimethylcyclohexylamine;

Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine);

Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and diethylenetriamine;

m-Phenylenebis(methylamine);

2,4,6-Tris(dimethylaminomethyl)phenol;

Diethylenetriamine;

Phenol;

Bisphenol A

Signal word: Danger

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 2 of 13

Pictograms:**Hazard statements**

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H360F	May damage fertility.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P201	Obtain special instructions before use.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P310	Immediately call a POISON CENTER/doctor.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Additional advice on labelling

For distribution to the general public:
 P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of the reach of children.

2.3. Other hazards

Contains Amines. May produce an allergic reaction.
 Use only outdoors or in a well-ventilated area.

SECTION 3: Composition/information on ingredients
3.2. Mixtures

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 3 of 13

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
2855-13-2	3-Aminomethyl-3,5,5-trimethylcyclohexylamine			30 - < 40 %
	220-666-8	612-067-00-9	01-2119514687-32	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H312 H302 H314 H318 H317 H412			
1950616-36-0	Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)			15 - < 25 %
	701-207-5		01-2119966906-20	
	Skin Corr. 1C, Skin Sens. 1B, Aquatic Chronic 3; H314 H317 H412			
77138-45-5	Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and diethylenetriamine			15 - < 25 %
	500-263-6		01-2120769506-44	
	Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1; H314 H318 H317			
1477-55-0	m-Phenylenebis(methylamine)			15 - < 25 %
	216-032-5		01-2119480150-50	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1B, Aquatic Chronic 3; H332 H302 H314 H317 H412			
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol			5 - < 10 %
	202-013-9		01-2119560597-27	
	Skin Corr. 1B, Skin Sens. 1B, Aquatic Chronic 3; H314 H317 H412			
100-51-6	Benzyl alcohol			5 - < 10 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319			
111-40-0	Diethylenetriamine			5 - < 10 %
	203-865-4	612-058-00-X	01-2119473793-27	
	Acute Tox. 2, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, STOT SE 3; H330 H312 H302 H314 H317 H335			
108-95-2	Phenol			1 - < 5 %
	203-632-7	604-001-00-2	01-2119471329-32	
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, STOT RE 2; H341 H331 H311 H301 H314 H318 H373			
71074-89-0	Bis[(dimethylamino)methyl]phenol			1 - < 5 %
	275-162-0			
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1; H302 H314 H318			
80-05-7	Bisphenol A			1 - < 5 %
	201-245-8	604-030-00-0	01-2119457856-23	
	Repr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3; H360F H318 H317 H335			

Full text of H and EUH statements: see section 16.

Further Information

SVHC list (Candidate List of Substances of Very High Concern for authorization): The product contains one of the listed substances: Bisphenol A

SECTION 4: First aid measures

4.1. Description of first aid measures

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 4 of 13

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Suspected of causing genetic defects.
May damage fertility.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam.
Extinguishing powder
Water spray jet
Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic
Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 5 of 13

taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage
7.1. Precautions for safe handling**Advice on safe handling**

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong, Organic peroxides

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature 5-35°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection
8.1. Control parameters**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-40-0	2,2'-Iminodi(ethylamine)	1	4.3		TWA (8 h)	WEL
80-05-7	Bisphenol A, inhalable dust	-	10		TWA (8 h)	WEL
108-95-2	Phenol	2	7.8		TWA (8 h)	WEL
		4	16		STEL (15 min)	WEL

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 6 of 13

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke. Avoid contact during pregnancy and while nursing.

Eye/face protection

Wear eye protection/face protection. Safety goggles with side shields are recommended.

Hand protection

Recommended material: NBR (Nitrile rubber)
Breakthrough time: > 480 min
Thickness of the glove material: 0,7 mm
DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles)

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Paste	
Colour:	black / red	
Odour:	characteristic	
pH-Value:		not applicable

Changes in the physical state

Melting point:		not determined
Initial boiling point and boiling range:		not determined
Flash point:		not applicable

Flammability

Solid:		not determined
Gas:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined

Auto-ignition temperature

Solid:		not determined
Gas:		not applicable
Decomposition temperature:		not determined

Oxidizing properties

Not oxidising.

Vapour pressure:		not determined
Density (at 20 °C):		1,07 g/cm ³
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 7 of 13

Solubility in other solvents

not determined

Partition coefficient:

not determined

Vapour density:

not determined

Evaporation rate:

not determined

9.2. Other information

Solid content:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****ATEmix calculated**

ATE (oral) 954,1 mg/kg; ATE (dermal) 1928,8 mg/kg; ATE (inhalation vapour) 5,40 mg/l; ATE (inhalation aerosol) 0,577 mg/l

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 8 of 13

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2855-13-2	3-Aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	LD50 mg/kg 1030	Rat		
	dermal	ATE mg/kg 1100			
1477-55-0	m-Phenylenebis(methylamine)				
	oral	LD50 mg/kg 930	Rat		
	dermal	LD50 mg/kg 2000	Rabbit		
	inhalation (1 h) vapour	LC50 3,89 mg/l	Rat		
	inhalation aerosol	ATE 1,5 mg/l			
100-51-6	Benzyl alcohol				
	oral	LD50 mg/kg 1230	Rat	GESTIS	
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			
111-40-0	Diethylenetriamine				
	oral	LD50 mg/kg 1080	Rat		
	dermal	LD50 mg/kg 1054	Rabbit		
	inhalation vapour	ATE 0,5 mg/l			
	inhalation aerosol	ATE 0,05 mg/l			
108-95-2	Phenol				
	oral	LD50 mg/kg 317	Rat		
	dermal	ATE mg/kg 300			
	inhalation vapour	ATE 3 mg/l			
	inhalation aerosol	ATE 0,5 mg/l			
71074-89-0	Bis[(dimethylamino)methyl]phenol				
	oral	ATE mg/kg 500			
80-05-7	Bisphenol A				
	oral	LD50 mg/kg 3250	Rat		
	dermal	LD50 mg/kg 3000	Rabbit		

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
111-40-0	Diethylenetriamine					
	Acute fish toxicity	LC50	430 mg/l	96 h	Leuciscus idus	
	Acute algae toxicity	ErC50 mg/l	1164	72 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 mg/l	53,5	48 h	Daphnia magna	
108-95-2	Phenol					
	Acute algae toxicity	ErC50	229 mg/l	72 h		GESTIS
80-05-7	Bisphenol A					
	Acute fish toxicity	LC50	4,6 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	2,73	96 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50	3,9 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2855-13-2	3-Aminomethyl-3,5,5-trimethylcyclohexylamine	1,9
100-51-6	Benzyl alcohol	1,05
111-40-0	Diethylenetriamine	-2,13
108-95-2	Phenol	1,5
80-05-7	Bisphenol A	3,32

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

The following waste code numbers from the European Waste Catalog (EWC) are considered as recommendations.

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 10 of 13

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Classification code: C8
 Special Provisions: 274
 Limited quantity: 1 kg
 Excepted quantity: E2
 Transport category: 3
 Hazard No: 80
 Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Classification code: C8
 Special Provisions: 274
 Limited quantity: 1 kg
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8

according to Regulation (EC) No 1907/2006

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 11 of 13



Special Provisions: 223, 274
 Limited quantity: 1 kg
 Excepted quantity: E2
 EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Special Provisions: A3 A803
 Limited quantity Passenger: 5 kg
 Passenger LQ: Y844
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 859
 IATA-max. quantity - Passenger: 15 kg
 IATA-packing instructions - Cargo: 863
 IATA-max. quantity - Cargo: 50 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
 Bisphenol A

Restrictions on use (REACH, annex XVII):

Entry 3: 3-Aminomethyl-3,5,5-trimethylcyclohexylamine; 2,4,6-Tris(dimethylaminomethyl)phenol; Benzyl alcohol; Diethylenetriamine
 Entry 66: Bisphenol A

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)
 (SEVESO III):

Additional information

VOC content: 28,7 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 12 of 13

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water contaminating class (D):	2 - clearly water contaminating
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information
Changes

This data sheet contains changes from the previous version in section(s): 15.

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation
 (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
 ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 CAS: Chemical Abstracts Service
 CLP: Classification, Labeling and Packaging
 DMEL: Derived Minimal Effect level
 DNEL: Derived No Effect Level
 EC50: Effective concentration, 50%
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)
 IMDG: International Maritime Dangerous Goods Code
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 NOEC: No Observed Effect Concentration
 OECD: Organisation for Economic Co-operation and Development
 PBT: persistent, bioaccumulative and toxic
 vPvB: very persistent and very bioaccumulative
 PNEC: Predicted No Effect Concentration
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)
 VOC: Volatile organic compound
 Acute Tox. 2: Acute toxicity, Category 2
 Acute Tox. 3: Acute toxicity, Category 3
 Acute Tox. 4: Acute toxicity, Category 4
 Aquatic Chronic 3: Long-term aquatic hazard, Category 3
 Eye Dam. 1: Serious eye damage/eye irritation, Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2
 Repr. 1B: Reproductive toxicity, Category 1B
 Skin Sens. 1: Skin sensitization, Category 1
 Skin Sens. 1B: Skin sensitization, Category 1B
 STOT RE 2: Specific target organ toxicity (repeated exposure), Category 2
 STOT SE 3: Specific target organ toxicity (single exposure), Category 3

ResiFIX Pure Epoxy BRSF, Comp. B

Revision date: 16.04.2019

Product code: SDB0008

Page 13 of 13

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1B; H314	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Repr. 1B; H360F	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)