

CELO

Discover the new **FORCE ONE**

The most powerful, lightweight and ergonomic gas nailer



FORCE ONE " Best-in-class gas nailer"



Power

Unmatched 105J power for a superior capacity versus other gas nailers and battery actuated tools

Accuracy

High success rate performance on hard materials and optimal precision for seamless operation.

Dust protection

Effective steel mesh filter cover for higher tool protection and longer lifespan.

Accessibility

Slim and longer nose, higher balance, and lightweight characteristics, crucial for overhead applications.

Smart technology

Quick and easy depth adjustments, computer controlled fan, light trigger with security control, battery LED indicator, easy fuel cell load etc.

FORCE ONE Range & fuel cell

Code	Description	Box (Qty)	Outerbox
FONE20US	FORCE ONE Kit	1	
9GASFONE	Fuel cell 800 shots	1	20

FORCE ONE - XHA Premium nails

Code	Description	Box (Qty)	Outerbox
913800XHA	1/2 inch Premium XHA nails	800	4.000
917800XHA	11/16 inch Premium XHA nails	800	4.000
922800XHA	7/8 inch Premium XHA nails	800	4.000
927800XHA	1 - 1/8 inch Premium nails	800	4.000
932800XHA	1 - 1/4 inch Premium XHA nails	800	4.000
938800XHA	1 - 1/2 inch Premium XHA nails	800	4.000



- Special zinc plated nails for very hard concrete.
- High performance design for optimal efficiency.
- Fire approval.

	1/2"	11/16"	7/8"	1 - 1/8"	1 - 1/4"	1 - 1/2"
STEEL	●					
CONCRETE C25/30		●	●			
CONCRETE 20/25		●	●	●		
CONCRETE C20/25			●	●	●	
WOOD					●	●

● Recommended ● Enabled

FORCE ONE Battery & charger

Code	Description	Box (Qty)
FONEBAT	FORCE ONE battery	1
FONECAR	FORCE ONE charger	1

Technical data

Characteristic	Specification
HEIGHT	14.38"
WIDTH	4.88"
LENGTH	13.15"
WEIGHT	7.9 lbs. including battery
LOADING CAPACITY	22 nails
BATTERY	Battery (Part • GN703RN)
BATTERY CAPACITY	6V DC, 1.5 Ah
CHARGER	Charger (Part • GN70380)
POWER SOURCE	100 - 240V AC, 50 or 60 Hz
POWER CONSUMPTION (rated Output)	8 VA (10 V 800 mA)
CHARGING TIME	150 minutes at maximum
ACCESSORIES	Safety glasses, Carrying case, Battery, Charger, Jam clear tool
TEMPERATURE RANGE FOR USE	-5°C to 49°C






Kit includes:

- 1 x Force One nailer
- 1 x Safety glasses
- 2 x Ear plugs
- 2 x Batteries
- 1 x Charger
- 1 x Carrying case
- 1 x Jam clear tool



DIRECT IMPACT FIXINGS accessories for electrical & mechanical installations

Solutions to install pipes

Code	Description	Box (Qty)	Approvals
918ABT	1/2 inch EMT Conduit clamps	100	
925ABT	3/4 inch EMT Conduits clamp	50	
932ABT	1 inch EMT Conduit clamp	50	
942ABT	1-1/4 inch EMT Conduit clamp	25	
912F	3/8 inch MC one hole strap*	100	





ABT



MC

* (washer required to be nailed)

Cable fixings solutions

Code	Description	Box (Qty)	Approvals
912PFT	3/8 inch MC cable clip	100	
912DFT	3/8 inch MC Two cables clip	100	



PFT



DFT

Cable ties fixings solutions

Code	Description	Box (Qty)
9TBB	Cable tie donut, black, for ties up to 0.4 inch width	100
9GTRRB	Cable tie donut, gray, for ties up to 0.4 inch width	100





TBB



TBB

Solutions for fixing on ceilings

Code	Description	Box (Qty)	Approvals
9AAT	Ceiling clip for Steel wire attachments on ceilings	100	
9TV14	1/4 inch threaded rod hanger for fastening on ceilings	50	



AAT



ATV

Solutions to install junction boxes or electrical gutters

Code	Description	Box (Qty)
915 AW	3/5 inch metal washer for multiple applications	200



AW

FORCE ONE "Main advantages"



Clean and quiet: ideal for confined spaces



Computer controlled smart fan adjusts to environment



LED low battery indicator



Highly effective dust protection with metal mesh suction filter



Ultra-light trigger



Quick and easy depth adjustments

Main features



From 1/2" to 1 - 1/2" long nails for added versatility



Drives up to 3,000 fixings per charge




Easy to load fuel cell



Reversible belt loop hook

Base materials



Applications

- Attaching light gauge steel track to concrete, concrete masonry bloc (CMU) or steel.
- Attaching plywood to concrete or concrete masonry block (CMU).
- Attaching lath to concrete, concrete masonry block (CMU) or steel.
- Attaching furring strips to concrete or concrete masonry block (CMU).
- Attaching special assembly accessories to concrete masonry block (CMU).



Small Things Matter

CELO Fixings USA INC.
2727 Ponce de León Blvd.
Coral Gables FL 3314

M +1 786 451 6106

www.thesmartclamps.com



All technical information is described in CELO's website including applications and installation instructions. The owner of the product is responsible to read, understand and acknowledge the use and maintenance as indicated by CELO. The individual user remains responsible for the correct use of the product. All usages not described by CELO are at one's own risk and responsibility. CELO will accept no responsibility or liability in respect of misuse or improper use of the product.